



28

## 4-Bolt Gauge Port Adapter/O-Ring Spacer

STANDARD PRESSURE : CODE 61

FLANGE SIZE	PART NO.	THREAD A	B	E	G	H	I	L	DRILLED DIA.			O-RING	WT
									M	MIN O	MAX O		
3/4"	13045-12-12	--	0.74	0.94	2.56	1.875	0.875	1.97	0.43	1.250	1.255	-214	1.35
3/4"	23045-12-12	1/4 NPTF	0.74	0.94	2.56	1.875	0.875	1.97	0.43	1.250	1.255	-214	1.32
3/4"	33045-12-12	7/16-20	0.74	0.94	2.56	1.875	0.875	1.97	0.43	1.250	1.255	-214	1.32
1"	13045-16-16	--	0.94	0.94	2.76	2.062	1.031	1.97	0.43	1.560	1.565	-219	1.35
1"	23045-16-16	1/4 NPTF	0.94	0.94	2.76	2.062	1.031	1.97	0.43	1.560	1.565	-219	1.32
1"	33045-16-16	7/16-20	0.94	0.94	2.76	2.062	1.031	1.97	0.43	1.560	1.565	-219	1.32
1 1/4"	13045-20-20	--	1.26	0.91	3.19	2.312	1.188	2.76	0.49	1.750	1.755	-222	1.68
1 1/4"	23045-20-20	1/4 NPTF	1.26	0.91	3.19	2.312	1.188	2.76	0.49	1.750	1.755	-222	1.65
1 1/4"	33045-20-20	7/16-20	1.26	0.91	3.19	2.312	1.188	2.76	0.49	1.750	1.755	-222	1.65
1 1/2"	13045-24-24	--	1.50	0.94	3.74	2.750	1.406	3.07	0.53	2.115	2.125	-225	1.79
1 1/2"	23045-24-24	1/4 NPTF	1.50	0.94	3.74	2.750	1.406	3.07	0.53	2.115	2.125	-225	1.76
1 1/2"	33045-24-24	7/16-20	1.50	0.94	3.74	2.750	1.406	3.07	0.53	2.115	2.125	-225	1.76
2"	13045-32-32	--	1.97	0.94	4.02	3.062	1.688	3.54	0.53	2.490	2.500	-228	2.80
2"	23045-32-32	1/4 NPTF	1.97	0.94	4.02	3.062	1.688	3.54	0.53	2.490	2.500	-228	2.75
2"	33045-32-32	7/16-20	1.97	0.94	4.02	3.062	1.688	3.54	0.53	2.490	2.500	-228	2.75

HIGH PRESSURE : CODE 62

FLANGE SIZE	PART NO.	A	B	E	G	H	I	L	DRILLED DIA.			O-RING	WT
									M	MIN O	MAX O		
1/2"	16045-08-08	--	0.47	0.94	2.17	1.594	0.718	1.50	0.35	1.000	1.005	-210	0.71
1/2"	26045-08-08	1/4 NPTF	0.47	0.94	2.17	1.594	0.718	1.50	0.35	1.000	1.005	-210	0.69
1/2"	36045-08-08	7/16-20	0.47	0.94	2.17	1.594	0.718	1.50	0.35	1.000	1.005	-210	0.69
3/4"	16045-12-12	--	0.74	0.94	2.76	2.000	0.937	1.97	0.43	1.250	1.255	-214	1.10
3/4"	26045-12-12	1/4 NPTF	0.74	0.94	2.76	2.000	0.937	1.97	0.43	1.250	1.255	-214	1.06
3/4"	36045-12-12	7/16-20	0.74	0.94	2.76	2.000	0.937	1.97	0.43	1.250	1.255	-214	1.06
1"	16045-16-16	--	0.94	0.91	3.19	2.250	1.093	2.76	0.51	1.560	1.565	-219	1.32
1"	26045-16-16	1/4 NPTF	0.94	0.91	3.19	2.250	1.093	2.76	0.51	1.560	1.565	-219	1.25
1"	36045-16-16	7/16-20	0.94	0.91	3.19	2.250	1.093	2.76	0.51	1.560	1.565	-219	1.25
1 1/4"	16045-20-20	--	1.26	0.94	3.74	2.625	1.250	3.07	0.53	1.750	1.755	-222	2.00
1 1/4"	26045-20-20	1/4 NPTF	1.26	0.94	3.74	2.625	1.250	3.07	0.53	1.750	1.755	-222	1.88
1 1/4"	36045-20-20	7/16-20	1.26	0.94	3.74	2.625	1.250	3.07	0.53	1.750	1.755	-222	1.88
1 1/2"	16045-24-24	--	1.50	0.94	4.41	3.125	1.437	3.70	0.67	2.115	2.125	-225	2.98
1 1/2"	26045-24-24	1/4 NPTF	1.50	0.94	4.41	3.125	1.437	3.70	0.67	2.115	2.125	-225	2.80
1 1/2"	36045-24-24	7/16-20	1.50	0.94	4.41	3.125	1.437	3.70	0.67	2.115	2.125	-225	2.80
2"	16045-32-32	--	2.01	0.94	5.28	3.812	1.750	4.49	0.83	2.490	2.500	-228	4.45
2"	26045-32-32	1/4 NPTF	2.01	0.94	5.28	3.812	1.750	4.49	0.83	2.490	2.500	-228	4.20
2"	36045-32-32	7/16-20	2.01	0.94	5.28	3.812	1.750	4.49	0.83	2.490	2.500	-228	4.20