



## Connector Plates

### STANDARD PRESSURE : CODE 61

FLANGE SIZE	PART NO.	A	E	G	H	I	L	DRILLED DIA. M	WT
1/2"	CP3-08	0.51	0.12	2.13	1.500	0.688	1.80	0.35	0.02
3/4"	CP3-12	0.75	0.12	2.56	1.875	0.875	2.04	0.43	0.02
1"	CP3-16	0.98	0.12	2.75	2.062	1.031	2.30	0.43	0.02
1 1/4"	CP3-20	1.26	0.12	3.11	2.312	1.188	2.86	0.43	0.04
1 1/2"	CP3-24	1.50	0.12	3.70	2.750	1.406	3.24	0.53	0.04
2"	CP3-32	2.00	0.12	4.01	3.062	1.688	3.54	0.53	0.06
2 1/2" <sup>1</sup>	CP3-40	2.48	0.12	4.49	3.500	2.000	4.26	0.53	0.06
3" <sup>2</sup>	CP3-48	2.87	0.16	5.31	4.188	2.438	5.14	0.67	0.09

### STANDARD PRESSURE : CODE 62

FLANGE SIZE	PART NO.	A	E	G	H	I	L	DRILLED DIA. M	WT
1/2"	CP6-08	0.51	0.16	2.20	1.594	0.718	1.86	0.35	0.02
3/4"	CP6-12	0.67	0.16	2.80	2.000	0.937	2.36	0.43	0.02
1"	CP6-16	0.94	0.16	3.19	2.250	1.093	2.74	0.51	0.04
1 1/4"	CP6-20	1.22	0.16	3.74	2.625	1.250	3.04	0.59	0.06
1 1/2"	CP6-24	1.50	0.16	4.45	3.125	1.437	3.74	0.67	0.09
2"	CP6-32	2.00	0.16	5.24	3.812	1.750	4.48	0.83	0.11

<sup>1</sup> 2500 PSI max.

<sup>2</sup> 2000 PSI max.