



Split Flange Halves

STANDARD PRESSURE : CODE 61

FLANGE SIZE	PART NO. ²	A	B	C	D	E	G	H	J	L	DRILLED DIA. M	MOUNTING KIT INFORMATION			WT ²
												PART NO. ¹	O-RING	HHCS	
1/2"	13001-08-08	1.22	0.96	0.75	0.25	0.51	2.13	1.500	0.344	0.90	0.33	HK-080	-210	5/16-18x1-1/4	0.30
3/4"	13001-12-12	1.53	1.27	0.87	0.25	0.55	2.56	1.875	0.438	1.02	0.41	HK-100	-214	3/8-16x1-1/4	0.40
1"	13001-16-16	1.78	1.52	0.95	0.30	0.63	2.76	2.062	0.515	1.15	0.41	HK-102	-219	3/8-16x1-1/4	0.48
1 1/4"	13001-20-20	2.03	1.72	0.87	0.30	0.63	3.11	2.312	0.599	1.43	0.47	HK-104	-222	7/16-14x1-1/2	0.66
1 1/2"	13001-24-24	2.41	2.00	0.98	0.30	0.63	3.70	2.750	0.703	1.62	0.53	HK-106	-225	1/2-13x1-1/2	1.02
2"	13001-32-32	2.84	2.47	1.02	0.36	0.63	4.02	3.062	0.844	1.90	0.53	HK-108	-228	1/2-13x1-1/2	1.10
2 1/2" ³	13001-40-40	3.34	2.95	1.50	0.36	0.75	4.49	3.500	1.000	2.13	0.53	HK-110	-232	1/2-13x1-3/4	1.64
3" ⁴	13001-48-48	4.03	3.58	1.61	0.36	0.87	5.32	4.188	1.219	2.57	0.66	HK-112	-237	5/8-11x1-3/4	2.87
3 1/2" ⁵	13001-56-56	4.53	4.03	1.10	0.42	0.87	5.98	4.750	1.375	2.74	0.67	HK-114	-241	5/8-11x2	3.30
4" ⁵	13001-64-64	5.03	4.53	1.38	0.42	0.98	6.38	5.125	1.531	2.99	0.67	HK-116	-245	5/8-11x2	3.70
5" ⁵	13001-80-80	6.03	5.53	1.61	0.42	1.10	7.24	6.000	1.813	3.54	0.67	HK-118	-253	5/8-11x2-1/4	5.52

HIGH PRESSURE : CODE 62

FLANGE SIZE	PART NO. ²	A	B	C	D	E	G	H	J	L	DRILLED DIA. M	MOUNTING KIT INFORMATION			WT ²
												PART NO. ¹	O-RING	HHCS	
1/2"	16001-08-08	1.28	0.97	0.87	0.29	0.63	2.21	1.594	0.359	0.93	0.34	HK-401	-210	5/16-18x1-1/4	0.36
3/4"	16001-12-12	1.66	1.28	1.10	0.33	0.75	2.80	2.000	0.469	1.18	0.41	HK-402	-214	3/8-16x1-1-1/2	0.80
1"	16001-16-16	1.91	1.53	1.30	0.36	0.95	3.19	2.250	0.547	1.37	0.49	HK-403	-219	7/16-14x1-3/4	1.18
1 1/4"	16001-20-20	2.16	1.75	1.50	0.39	1.06	3.74	2.625	0.625	1.52	0.53	HK-404	-222	1/2-13x1-3/4	1.76
1 1/2"	16001-24-24	2.53	2.03	1.69	0.48	1.18	4.45	3.125	0.719	1.87	0.66	HK-405	-225	5/8-11x2-1/4	3.00
2"	16001-32-32	3.16	2.66	2.05	0.48	1.46	5.24	3.812	0.875	2.24	0.83	HK-406	-228	3/4-10x2-3/4	4.62

¹ Add a "K" to flange part # to include mounting hardware

⁴ 2000 PSI max.

² Includes both halves

⁵ 500 PSI max.

³ 2500 PSI max.