



Split Flange Halves – Low Profile

STANDARD PRESSURE : CODE 61

FLANGE SIZE	PART NO. ²	A	B	D	E	G	H	J	L	DRILLED DIA. M	MOUNTING KIT INFORMATION			WT ²
											PART NO. ¹	O-RING	HHCS	
1/2"	13003-08-08	1.22	0.96	0.25	0.51	2.13	1.500	0.344	0.90	0.35	HK-080	-210	5/16-18x1-1/4	0.13
3/4"	13003-12-12	1.53	1.27	0.25	0.55	2.56	1.875	0.438	1.02	0.43	HK-100	-214	3/8-16x1-1/4	0.15
1"	13003-16-16	1.78	1.52	0.30	0.63	2.75	2.062	0.515	1.15	0.43	HK-102	-219	3/8-16x1-1/4	0.22
1 1/4"	13003-20-20	2.03	1.72	0.30	0.63	3.11	2.312	0.594	1.44	0.43	HK-104	-222	7/16-14x1-1/2	0.33
1 1/2"	13003-24-24	2.41	2.00	0.30	0.63	3.70	2.750	0.703	1.62	0.51	HK-106	-225	1/2-13x1-1/2	0.40
2"	13003-32-32	2.84	2.47	0.36	0.63	4.02	3.062	0.844	1.90	0.51	HK-108	-228	1/2-13x1-1/2	0.49

HIGH PRESSURE : CODE 62

FLANGE SIZE	PART NO. ²	A	B	D	E	G	H	J	L	DRILLED DIA. M	MOUNTING KIT INFORMATION			WT ²
											PART NO. ¹	O-RING	HHCS	
1/2"	16003-08-08	1.28	0.97	0.29	0.63	2.21	1.594	0.359	0.93	0.35	HK-401	-210	5/16-18x1-1/4	0.35
3/4"	16003-12-12	1.66	1.28	0.33	0.79	2.80	2.000	0.469	1.18	0.43	HK-402	-214	3/8-16x1-1/2	0.70
1"	16003-16-16	1.91	1.53	0.36	0.98	3.19	2.250	0.547	1.37	0.51	HK-403	-219	7/16-14x1-3/4	1.10
1 1/4"	16003-20-20	2.16	1.75	0.39	1.06	3.74	2.625	0.625	1.52	0.59	HK-404	-222	1/2-13x1-3/4	1.50
1 1/2"	16003-24-24	2.53	2.03	0.48	1.18	4.45	3.125	0.719	1.87	0.67	HK-405	-225	5/8-11x2-1/4	2.42
2"	16003-32-32	3.16	2.66	0.48	1.46	5.24	3.812	0.875	2.24	0.83	HK-406	-228	3/4-10x2-3/4	4.49
2 1/2" ³	16003-40-40	4.29	3.54	0.81	1.77	7.09	4.875	1.157	2.96	1.02	HK-407	-232	7/8-9x3	9.02
3" ³	16003-48-48	5.22	4.53	1.00	2.17	8.47	6.000	1.409	3.90	1.26	HK-408	-237	1-1/8-7x3-1/2	18.92

¹ Add a "K" to flange part # to include mounting hardware.

² Includes both halves.

³ Not in SAE specifications.